

# MAC PLANTMASTER S.S.

The MAC Plantmaster is now available in full stainless steel to meet the growing demand for quality and durability



## KEY SPECIFICATION

Hot Water Static

12ltr, 15ltr or 21ltr/min  
Water Flow

100bar or 200bar Pressure

240v or 415v Power Supply

High Pressure Chemical

Full Frost Protection

# MAC PLANTMASTER S.S.



## STANDARD FEATURES

- High quality, full stainless steel cabinet
- Full frost protection and cabinet lagging
- Lockable stainless steel front door
- Efficient M2 boiler system
- Flame failure and leak detection
- 16lt fuel tank with low level sensor as standard
- Professional Interpump with ceramic pistons
- Industrial 1450rpm 4 pole electric Nicolini motor
- Automatic stop/start system
- High pressure chemical system
- Bypass and safety valve
- Burner control with flow switch and thermostat
- 24v low tension safety

## CHOOSE FROM A WHOLE HOST OF BESPOKE OPTIONS AND ACCESSORIES:

- Internal and external hose reels
- Upgraded fuel and water tanks
- Key fob and remote control systems
- Timed and non-timed chemical systems



FLAME FAILURE AND  
LEAK DETECTION SYSTEM



30 SECOND  
AUTO STOP/START

	PLANTMASTER/SS1	PLANTMASTER/SS2	PLANTMASTER/SS3	PLANTMASTER/SS4
<b>Water Flow</b>	12lt per minute	15lt per minute	15lt per minute	21lt per minute
<b>Pressure</b>	100bar, 1500psi	150bar, 2200psi	200bar, 3000psi	200bar, 3000psi
<b>Motor Specification</b>	3hp, 1450rpm	5.5hp, 1450rpm	7.5hp, 1450rpm	10hp, 1450rpm
<b>Chemical</b>	High Pressure	High Pressure	High Pressure	High Pressure
<b>Shutdown System</b>	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start
<b>Temperature</b>	0-100°C	0-100°C	0-100°C	0-100°C
<b>Power</b>	240v	415v	415v	415v
<b>Weight</b>	230kg	240kg	250kg	270kg
<b>Dimensions (h x w x d)</b>	160 x 82 x 56cm	160 x 82 x 56cm	160 x 82 x 56cm	160 x 82 x 56cm